



滑轮制造标准 | Pulley Manufacture Standard

3. 轮缘宽度 b 的允许偏差 t3

Allowable deviation t3 of pulley edge width b

轮缘号 Rim	t3
1	+2
2	
3	+3
4	
5	+4
6	
7	+5
8	

4. 外径 D1 的允许偏差 t4

Allowable deviation t4 of external diameter D

D1	t4
≤250	-0.5
> 250-500	1.0
> 500-1000	-1.5
> 1000-1200	-2.0
> 1200-1500	-2.5
> 1500-1800	-3.0
> 1800-2000	-3.5

滑轮系列表 Pulley Series Table

Do/d=25 (Do=D+d)

滑轮代号 Item No	钢丝绳直径 Diameter d(mm)	D	D1	R	b	w	f	D2	严密封型 Rigorous Sealing Type		一般密封型 General Sealing Type		轴承型号 Bearing	参考重量 Weight (kg)
									D3	B	D3	B		
WJ 1251 /WJ1251 A	>10-14	355	400	7	37	28	8	55	65	86	63	64	211	19
WJ 1252 /WJ1252 A								60	70	88	69	66	212	19
WJ 1253 /WJ1253 A								65	75	90	75	68	213	21
WJ 1254 /WJ1254 A								70	80	92	80	70	214	22
WJ 2251 /WJ2251 A	>14-20	450	510	10	50	38	8	80	90	96	90	74	216	33
WJ 2252 /WJ2252 A								85	95	100	96	78	217	35
WJ 2253 /WJ2253 A								90	105	108	102	82	218	37
WJ 2254 /WJ2254 A								95	110	112	108	86	219	39
WJ 3251 /WJ3251 A	>20-24	560	631	12	60	46	10	95	110	114	108	90	219	53
WJ 3252 /WJ3252 A								100	115	118	113	94	220	54
WJ 3253 /WJ3253 A								110	125	128	124	102	222	58
WJ 3254 /WJ3254 A								120	130	132	135	106	224	60
WJ 4251 /WJ4251 A	>24-30	710	800	15	73	57	10	130	140	134	146	106	226	98.5
WJ 4252 /WJ4252 A								140	160	138	158	110	228	101
WJ 4253 /WJ4253 A								150	170	144	170	116	230	105
WJ 4254 /WJ4254 A								160	180	154	180	122	232	109
WJ 5251 /WJ5251 A	>30-38	900	1012	19	92	72	12	160	190	156	188	128	42232	169
WJ 5252 /WJ5252 A								170	200	164	202	136	42234	175
WJ 5253 /WJ5253 A								180	220	164	212	136	42236	175
WJ 5254 /WJ5254 A								190	220	170	225	142	42238	180
WJ 6251 /WJ6251 A	>44-52	1000	1126	22	104	82	12	160	190	156	188	128	42232	215
WJ 6252 /WJ6252 A								170	200	164	202	136	42234	219
WJ 6253 /WJ6253 A								180	220	164	212	136	42236	219
WJ 6254 /WJ6254 A								190	220	170	225	142	42238	225
WJ 7251 /WJ7251 A	>44-52	1250	1402	26	123	98	14	190	220	172	225	148	42238	396
WJ 7252 /WJ7252 A								200	240	178	235	154	42240	398.2
WJ 7253 /WJ7253 A								220	260	196	260	168	42244	430.1
WJ 7254 /WJ7254 A								240	280	210	278	182	42248	408.1
WJ 8251 /WJ8251 A	>52-58	1400	1572	29	135	110	14	190	220	172	225	148	42238	507.1
WJ 8252 /WJ8252 A								200	240	178	235	154	42240	507.1
WJ 8253 /WJ8253 A								220	260	196	260	168	42244	213.4
WJ 8254 /WJ8254 A								240	280	210	278	182	42248	522.5